### The new Sentinel Door: Industrial Quality, Security bolts, Security rebate, Extension frames, Choice of exit locks, Rain canopy



## Sentinel Door MZ-1

A quality door for multiple applications



#### www.thegaragedoorcentre.co.uk

# MZ Sentinel Steel Door

4

5

Lock Cassette

EPDM seal

Rain Canopy optional

6



**Possible applications** 

- private use as well as use in trade and industry
- construction containers
- basement
- side doors for gate openings
- escape doors with anti-panic feature







Spring hinge, adjustable hinge



2 Security bolts

#### Product features


- 1. Door leaf 45 mm thick, made of 0.9 mm steel, rebate on three sides, powder-coated surface finish for long-lasting protection
- 2. Spring hinge for automatic closing and adjustable hinge for easy fitting on site
- 3. Two security bolts for anti-theft
- 4. Blank unprepared for surface or integral locking
- 5. EPDM seal on 3 sides for improved thermal and sound insulation
- 6. Rain canopy to protect from water ingress

Thermal insulation of door leaf: 1.7 W/m<sup>2</sup>K Sound insulation of door leaf: approx. 39 dB Fitting to: concrete, brickwork, gas concrete, steel, partition walls

#### **Dimensions (mm)**

Door set (Nominal)		Structural Opening Width		
Ordering	Over-all	Standard	Extension	
Size	Frame	Frame	Frame	
Width x Height	Width x Height	Width x Height	type A	type B
900 x 2100	890 x 2085	895 x 2090	up to 925	up to 950
1000 x 2100	990 x 2085	995 x 2090	up to 1025	up to 1050
1120 x 2100	1110 x 2085	1115 x 2090	up to 1145	up to 1170

Above size held in stock, special sizes are available on request.



A quality product, engineered for multiple applications at our dedicated production facility, offering a flexible range of fitting extras



Available in a range of colours custom-made to RAL colour chart



Choose from a wide range of options

**Optional extras** 







Single point panic

Door closer



Friction door stay



Aluminium threshold

**Dimensions in mm** 

Steel threshold

Handing LH or RH



Glazing Retrofit glazing kits available on request



#### Optional, adjustable extension frame

95

82.5

nax.




Extension frame type A small, shift from 0-25 mm (extendable up to 12.5 mm on each side) max. 82.5 12.5 70

50

#### Extension frame type B

large, shift from 25-50 mm

(extendable up to an additional 12.5mm on each side)



www.thegaragedoorcentre.co.uk